

Data Sheet
ADMV7710
FEATURES


- Gain: 24 dB typical**
- Output power for 1 dB compression: 28 dBm typical**
- Saturated output power: 29 dBm typical**
- Output third-order intercept: 34 dBm typical**
- Input return loss: 18 dB typical**
- Output return loss: 10 dB typical**
- DC supply: 4 V at 800 mA**
- No external matching required**
- Die size: 2.999 mm × 3.999 mm × 0.05 mm**

APPLICATIONS

- E-band communication systems**
- High capacity wireless backhaul radio systems**
- Test and measurement**

GENERAL DESCRIPTION

The ADMV7710 is an integrated, E-band, gallium arsenide (GaAs), pseudomorphic, high electron mobility tranfer (pHEMT), mono-lithic microwave integrated circuit (MMIC), medium power amplifier with an on-chip, temperature compensated power detector that operates from 71 GHz to 76 GHz. The ADMV7710 provides 24 dB of gain, 28 dBm of output power at 1 dB compression, and 29 dBm of saturated output power at 20% power added efficiency from a 4 V power supply. The ADMV7710 exhibits excellent linearity and is optimized for E-band communications and high capacity, wireless backhaul radio systems. The amplifier configuration and high gain make the device an excellent candidate for last stage signal amplification before the antenna. All data is taken with the chip in a $50\ \Omega$ test fixture connected via a 3 mil wide \times 0.5 mil thick \times 7 mil long ribbon on each port. The ADMV7710 is available in a 40-pad bare die (CHIP) and operates over the -55°C to $+85^{\circ}\text{C}$ temperature range.

FUNCTIONAL BLOCK DIAGRAM

Figure 1.
16408-001
Rev. A
Document Feedback

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 ©2018 Analog Devices, Inc. All rights reserved.
Technical Support www.analog.com

TABLE OF CONTENTS

Features	1	Theory of Operation	14
Applications.....	1	Applications Information	15
General Description	1	Assembly Diagram	16
Functional Block Diagram	1	Mounting and Bonding Techniques for Millimeterwave GaAs	
Revision History	2	MMICs.....	17
Specifications.....	3	Handling Precautions	17
Absolute Maximum Ratings.....	4	Mounting	17
Thermal Resistance	4	Wire Bonding.....	17
ESD Caution.....	4	Outline Dimensions	18
Pin Configuration and Function Descriptions.....	5	Ordering Guide	18
Interface Schematics.....	6		
Typical Performance Characteristics	7		

REVISION HISTORY

12/2018—Rev. 0 to Rev. A

Changes to Figure 42.....	12
Changes to Figure 43 and Figure 44.....	13
Added Figure 45; Renumbered Sequentially	13
Changes to Ordering Guide	18

3/2018—Revision 0: Initial Version

SPECIFICATIONS

$T_A = 25^\circ\text{C}$, VDD_{xA} and $\text{VDD}_{\text{xB}} = 4 \text{ V}$, $I_{\text{DD}} = 800 \text{ mA}$, unless otherwise noted.

Table 1.

Parameter	Symbol	Min	Typ	Max	Unit
OPERATING CONDITIONS					
Frequency Range		71		76	GHz
PERFORMANCE					
Gain		21	24		dB
Gain Variation over Temperature			0.02		dB/ $^\circ\text{C}$
Output Power for 1 dB Compression	OP1dB	26	28		dBm
Saturated Output Power	P_{SAT}		29		dBm
Output Third-Order Intercept at Maximum Gain ¹	OIP3		34		dBm
Power Added Efficiency	PAE		20		%
Input Return Loss			18		dB
Output Return Loss			10		dB
POWER SUPPLY					
Total Drain Current ²	I_{DD}		800		mA

¹ Data taken at output power (P_{out}) = 14 dBm per tone, 1 MHz spacing.

² Adjust the VGGxA and VGGxB pads from -2 V to 0 V to achieve the total drain current (I_{DD}) = 800 mA.

ABSOLUTE MAXIMUM RATINGS

Table 2.

Parameter	Rating
Drain Bias Voltage (VDD1A to VDD4A, VDD1B to VDD4B)	4.5 V
Gate Bias Voltage (VGG1A to VGG4A, VGG1B to VGG4B)	-3 V to 0 V
Maximum Junction Temperature (to Maintain 1 Million Hours Mean Time to Failure (MTTF))	175°C
Operating Temperature Range	-55°C to +85°C
Storage Temperature Range	-65°C to +150°C
Electrostatic Discharge (ESD) Sensitivity Human Body Model (HBM)	150 V

Stresses at or above those listed under Absolute Maximum Ratings may cause permanent damage to the product. This is a stress rating only; functional operation of the product at these or any other conditions above those indicated in the operational section of this specification is not implied. Operation beyond the maximum operating conditions for extended periods may affect product reliability.

THERMAL RESISTANCE

Thermal performance is directly linked to printed circuit board (PCB) design and operating environment. Careful attention to PCB thermal design is required.

θ_{JC} is the junction to case (or die to package) thermal resistance.

Table 3. Thermal Resistance

Package Type	θ_{JC}^1	Unit
C-40-2	24.2	°C/W

¹ Based on the ATROX 800HT1V® as the die attach epoxy.

ESD CAUTION



ESD (electrostatic discharge) sensitive device.

Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

PIN CONFIGURATION AND FUNCTION DESCRIPTIONS




Figure 2. Pad Configuration


Table 4. Pad Function Descriptions

Pad No.	Mnemonic	Description
1, 3, 5, 7, 9, 11, 13, 15, 17, 19, 20, 22, 25, 27, 29, 31, 33, 35, 37, 39	GND	Ground Connection (See Figure 3).
2	RFIN	RF Input. AC-couple RFIN and match it to 50 Ω (see Figure 4).
4, 8, 12, 16	VGG1A to VGG4A	First Stage Gate Bias Voltage for the Power Amplifier (See Figure 8). For the required external components, see Figure 47.
6, 10, 14, 18	VDD1A to VDD4A	First Stage Drain Bias Voltage for the Power Amplifier (See Figure 5).
21	RFOUT	RF Output. AC-couple RFOUT and match it to 50 Ω (see Figure 6).
23	VREF	Reference Voltage for the Power Detector (See Figure 7). VREF is the dc bias of the diode biased through an external resistor used for temperature compensation of VDET. Refer to the typical application circuit (see Figure 47) for the required external components.
24	VDET	Detector Voltage for the Power Detector (See Figure 7). VDET is the dc voltage representing the RF output power rectified by the diode, which is biased through an external resistor. Refer to the typical application circuit (see Figure 47) for the required external components.
26, 30, 34, 38	VDD4B to VDD1B	Second Stage Drain Bias Voltage for the Power Amplifier (See Figure 5).
28, 32, 36, 40	VGG4B to VGG1B	Second Stage Gate Bias Voltage for the Power Amplifier (See Figure 8). For the required external components, see Figure 47.
Die Bottom	GND	Ground. The die bottom must be connected to the RF/dc ground (see Figure 3).

INTERFACE SCHEMATICS


16408-003

Figure 3. GND Interface Schematic



16408-006

Figure 6. RFOUT Interface Schematic




16408-004

Figure 4. RFIN Interface Schematic



16408-007


Figure 7. VREF, VDET Interface Schematic



16408-005

VDD1A TO VDD4A
VDD1B TO VDD4B

Figure 5. VDD1A to VDD4A and VDD1B to VDD4B Interface Schematic




16408-008


VGG1A TO VGG4A
VGG1B TO VGG4B

Figure 8. VGG1A to VGG4A and VGG1B to VGG4B Interface Schematic


TYPICAL PERFORMANCE CHARACTERISTICS




16408-009




16408-012

Figure 9. Broadband Gain and Return Loss Response vs. Frequency, $I_{DD} = 800 \text{ mA}$ 


16408-010




16408-013

Figure 10. Gain vs. Frequency over Various Temperatures, $I_{DD} = 800 \text{ mA}$ 


16408-011




16408-014




16408-016




16408-016




16408-017




16408-018




16408-019




16408-020




16408-021




16408-024




16408-022



16408-025



16408-023



16408-026




Figure 27. Gain, Output P_{1dB} , and P_{SAT} vs. Drain Current (I_{DD}), $RF = 76$ GHz




Figure 30. Gain, P_{OUT} , PAE, and I_{DD} vs. Input Power, $RF = 76$ GHz, $I_{DD} = 700$ mA




Figure 28. Gain, P_{OUT} , PAE, and I_{DD} vs. Input Power, $RF = 71$ GHz, $I_{DD} = 700$ mA




Figure 31. Gain, P_{OUT} , PAE, and I_{DD} vs. Input Power, $RF = 71$ GHz, $I_{DD} = 800$ mA




Figure 29. Gain, P_{OUT} , PAE, and I_{DD} vs. Input Power, $RF = 73.5$ GHz, $I_{DD} = 700$ mA




Figure 32. Gain, P_{OUT} , PAE, and I_{DD} vs. Input Power, $RF = 73.5$ GHz, $I_{DD} = 800$ mA




Figure 33. Gain, P_{OUT} , PAE, and I_{DD} vs. Input Power, RF = 76 GHz,
 $I_{DD} = 800$ mA




Figure 36. Gain, P_{OUT} , PAE, and I_{DD} vs. Input Power, RF = 76 GHz,
 $I_{DD} = 900$ mA




Figure 34. Gain, P_{OUT} , PAE, and I_{DD} vs. Input Power, RF = 71 GHz,
 $I_{DD} = 900$ mA




Figure 37. Power Dissipation vs. Input Power over Various Frequencies,
 $I_{DD} = 700$ mA, $T_A = 85^\circ\text{C}$




Figure 35. Gain, P_{OUT} , PAE, and I_{DD} vs. Input Power, RF = 73.5 GHz,
 $I_{DD} = 900$ mA







Figure 38. Power Dissipation vs. Input Power over Various Frequencies,
 $I_{DD} = 800$ mA, $T_A = 85^\circ\text{C}$




16408-039






16408-041



16408-040



16408-042



THEORY OF OPERATION

The circuit architecture of the ADMV7710 power amplifier is shown in Figure 46. The ADMV7710 uses four cascaded gain stages to form an amplifier with a combined gain of 24 dB and a saturated output power (P_{SAT}) of 29 dBm. At the output of the last stage, a coupler taps off a small portion of the output signal.

The coupled signal is presented to an on-chip diode detector for external monitoring of the output power. A matched reference diode is included to correct detector temperature dependencies. See the application circuit shown in Figure 47 for further details on biasing the different blocks and using the detector features.




Figure 46. Power Amplifier Circuit Architecture

16408-045

APPLICATIONS INFORMATION

A typical application circuit for the ADMV7710 is shown in Figure 47. Combine the supply lines as shown in the application circuit schematic to minimize the external component count and to simplify power supply routing.

The ADMV7710 uses several amplifier, detector, and attenuator stages. All stages use depletion mode pHEMT transistors. It is important to use the following power-up bias sequence to avoid transistor damage:

1. Apply a -2 V bias to the VGG1A to VGG4A and VGG1B to VGG4B pads.




Figure 47. Typical Application Circuit

ASSEMBLY DIAGRAM




Figure 48. Assembly Diagram

16108-047

MOUNTING AND BONDING TECHNIQUES FOR MILLIMETERWAVE GaAs MMICS

Attach the die directly to the ground plane eutectically or with conductive epoxy.

To bring RF to and from the chip, use $50\ \Omega$ microstrip transmission lines on 0.127 mm (5 mil) thick alumina thin film substrates (see Figure 49).




Figure 49. Routing RF Signals

To minimize bond wire length, place microstrip substrates as close to the die as possible. Typical die to substrate spacing is 0.076 mm to 0.152 mm (3 mil to 6 mil).

HANDLING PRECAUTIONS

To avoid permanent damage, adhere to the following precautions.

Storage

All bare die ship in either waffle or gel-based ESD protective containers, sealed in an ESD protective bag. After opening the sealed ESD protective bag, all die must be stored in a dry nitrogen environment.

Cleanliness

Handle the chips in a clean environment. Never use liquid cleaning systems to clean the chip.

Static Sensitivity

Follow ESD precautions to protect against ESD strikes.

Transients

Suppress instrument and bias supply transients while bias is applied. To minimize inductive pickup, use shielded signal and bias cables.

General Handling

Handle the chip on the edges only using a vacuum collet or with a sharp pair of bent tweezers. Because the surface of the chip has fragile air bridges, never touch the surface of the chip with a vacuum collet, tweezers, or fingers.

MOUNTING

The chip is back metallized and can be die mounted with gold/tin (AuSn) eutectic preforms or with electrically conductive epoxy. The mounting surface must be clean and flat.

Eutectic Die Attach

It is best to use an 80% Au/20% Sn preform with a work surface temperature of 255°C and a tool temperature of 265°C. When hot 90% nitrogen/10% hydrogen gas is applied, maintain tool tip temperature at 290°C. Do not expose the chip to a temperature greater than 320°C for more than 20 sec. No more than 3 sec of scrubbing is required for attachment.


Epoxy Die Attach

ATROX 800HT1V is recommended for die attachment. Apply a minimum amount of epoxy to the mounting surface so that a thin epoxy fillet is observed around the perimeter of the chip after placing it into position. Cure the epoxy per the schedule provided by the manufacturer.

WIRE BONDING

RF bonds made with 3 mil \times 0.5 mil gold ribbon are recommended for the RF ports. These bonds must be thermosonically bonded with a force of 40 g to 60 g. DC bonds of 1 mil (0.025 mm) diameter, thermosonically bonded, are recommended. Create ball bonds with a force of 40 g to 50 g and wedge bonds with a force of 18 g to 22 g. Create all bonds with a nominal stage temperature of 150°C. Apply a minimum amount of ultrasonic energy to achieve reliable bonds. Keep all bonds as short as possible, less than 12 mil (0.31 mm).

OUTLINE DIMENSIONS



*Figure 50. 40-Pad Bare Die [CHIP]
(C-40-2)
Dimensions shown in millimeters*

11-14-2017-A

ORDERING GUIDE

Model^{1, 2}	Temperature Range	Package Description	Package Option
ADMV7710CHIPS	–55°C to +85°C	40-Pad Bare Die [CHIP]	C-40-2
ADMV7710-SX	–55°C to +85°C	40-Pad Bare Die [CHIP]	C-40-2

¹ The ADMV7710-SX consists of two pairs of the die in a gel pack for sample orders.

² This is a gel pack option; contact Analog Devices, Inc., sales representatives for additional packaging options.